

Manual Supplement

Manual Title:	5080A Operators	Supplement Issue:	2
Print Date:	July 2012	Issue Date:	6/15
Revision/Date:		Page Count:	1

This supplement contains information necessary to ensure the accuracy of the above manual.
This manual is distributed as an electronic manual on the following CD-ROM:

CD Title:	5080A
CD Rev. & Date:	3, 11/2011
CD PN:	3502934

FLUKE®

Calibration

Change #1, 64917, 397

On page 1-3, under **Safety Information**, delete the first sentence and all the bullets.

On page 1-4, under the **Symbols** table, delete the CAT I information and add the following:

	Conforms to relevant South Korean EMC Standards.
---	--

On page 1-7, under **General Specifications**, replace the Safety and EMC sections:

Safety.....	IEC 61010-1: Overvoltage category II, Pollution Degree 2
Electromagnetic Compatibility (EMC)	
International	IEC 61326-1: Basic Electromagnetic Environment
	CISPR 11: Group 1, Class A
	<i>Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself.</i>
	<i>Class A: Equipment is suitable for use in all establishments other than domestic and those directly connected to a low-voltage power supply network that supplies buildings used for domestic purposes. There may be potential difficulties in ensuring electromagnetic compatibility in other environments due to conducted and radiated disturbances.</i>
	<i>Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object.</i>
Korea (KCC)	Class A Equipment (Industrial Broadcasting & Communication Equipment)
	<i>Class A: Equipment meets requirements for industrial electromagnetic wave equipment and the seller or user should take notice of it. This equipment is intended for use in business environments and not to be used in homes.</i>
USA (FCC).....	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.

On page 1-9, in the **Resistance** table, add note [5] to the table head of the **Full Specs Load** and the **Max Peak Current** columns and add note 5.

[5] I_{max} and Max Peak Current are limited to 150 mA for the 0 Ω to 19 Ω resistors in COMP 2-wire mode.