

Manual Supplement

| | | | |
|---------------|-----------------|-------------------|------|
| Manual Title: | 5502A Operators | Supplement Issue: | 4 |
| Print Date: | September 2012 | Issue Date: | 9/18 |
| Revision/Date | | Page Count: | 19 |

This supplement contains information necessary to ensure the accuracy of the above manual.
This manual is distributed as an electronic manual on the following CD-ROM:

| | |
|-----------------|---------|
| CD Title: | 5502A |
| CD Rev. & Date: | 11/2012 |
| CD PN: | 4155227 |

FLUKE®

Calibration

Change #1, 66379, 561, 562, 564

On pages 1-9 through 1-28, replace the entire **Specifications** section with:

General Specifications

The following tables list the 5502A specifications. All specifications are valid after allowing a warm-up period of 30 minutes, or twice the time the 5502A has been turned off. (For example, if the 5502A has been turned off for 5 minutes, the warm-up period is 10 minutes.)

All specifications apply for the temperature and time period indicated. For temperatures outside of $t_{cal} \pm 5^\circ\text{C}$ (t_{cal} is the ambient temperature when the 5502A was calibrated), the temperature coefficient as stated in the General Specifications must be applied.

The specifications also assume the Calibrator is zeroed every 7 days or whenever the ambient temperature changes more than 5°C . The tightest ohms specifications are maintained with a zero cal every 12 hours within $\pm 1^\circ\text{C}$ of use.

Also see additional specifications later in this chapter for information on extended specifications for ac voltage and current.

Warmup Time Twice the time since last warmed up, to a maximum of 30 minutes.

Settling Time Less than 5 seconds for all functions and ranges except as noted.

Standard Interfaces IEEE-488 (GPIB), RS-232

Temperature

Operating 0°C to 50°C

Calibration (t_{cal}) 15°C to 35°C

Storage -20°C to $+70^\circ\text{C}$; The DC current ranges 0 to 1.09999 A and 1.1 A to 2.99999 A are sensitive to storage temperatures above 50°C . If the 5502A is stored above 50°C for greater than 30 minutes, these ranges must be re-calibrated. Otherwise, the 90 day and 1 year uncertainties of these ranges double.

Temperature Coefficient Temperature coefficient for temperatures outside of $t_{cal} \pm 5^\circ\text{C}$ is 10 % of the stated specification per $^\circ\text{C}$.

Relative Humidity

Operating $<80\%$ to 30°C , $<70\%$ to 40°C , $<40\%$ to 50°C

Storage $<95\%$, non-condensing. After long periods of storage at high humidity, a drying-out period (with power on) of at least one week may be required.

Altitude

Operating 3050 m (10 000 ft) maximum at $\leq 120\text{ V}$ line voltage operation
2,000 m (6 500 ft) maximum at $> 120\text{ V}$ line voltage operation

Non-operating 12 200 m (40 000 ft) maximum

Safety IEC 61010-1: Overvoltage CAT II, Pollution Degree 2

Output Terminal Electrical Overload Protection Provides reverse-power protection, immediate output disconnection, and/or fuse protection on the output terminals for all functions. This protection is for applied external voltages up to $\pm 300\text{ V}$ peak.

Analog Low Isolation 20 V normal operation, 400 V peak transient

Electromagnetic Compatibility

International IEC 61326-1: Controlled Electromagnetic Environment; IEC 61326-2-1
CISPR 11: Group 1, Class A

*Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself.
Class A: Equipment is suitable for use in all establishments other than domestic and those directly connected to a low-voltage power supply network that supplies buildings used for domestic purposes. There may be potential difficulties in ensuring electromagnetic compatibility in other environments due to conducted and radiated disturbances.*

Caution: This equipment is not intended for use in residential environments and may not provide adequate protection to radio reception in such environments.

Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object.

The equipment may not meet the immunity requirements of this standard when test leads and/or test probes are connected.

If used in areas with electromagnetic fields of 1 V/m to 3 V/m from 0.08 GHz to 1 GHz, resistance outputs have a floor adder of $0.508\ \Omega$. Performance not specified above 3 V/m. This instrument may be susceptible to electro-static discharge (ESD) to the binding posts. Good static awareness practices should be followed when handling this and other pieces of electronic equipment. Additionally, this instrument may be susceptible to electrical fast transients on the mains terminals. If any disturbances in operation are observed, it is recommended that the rear-panel chassis ground terminal

be connected to a known good earth ground with a low-inductance ground strap. Note that a mains power outlet, while providing a suitable ground for protection against electric shock hazard, may not provide an adequate ground to properly drain away conducted rf disturbances and may, in fact, be the source of the disturbance. This instrument was certified for EMC performance with data I/O cables not in excess of 3 m.

- Line Power** Line Voltage (selectable): 100 V, 120 V, 220 V, 240 V
 Line Frequency: 47 Hz to 63 Hz
 Line Voltage Variation: $\pm 10\%$ about line voltage setting. For optimal performance at full dual outputs (e.g. 1000 V, 20 A) choose a line voltage setting that is $\pm 7.5\%$ from nominal.
- Power Consumption** 600 VA
- Dimensions (HxWxL)** 17.8 cm x 43.2 cm x 47.3 cm (7 in x 17 in x 18.6 in) Standard rack width and rack increment, plus 1.5 cm (0.6 in) for feet on bottom of unit.
- Weight (without options)** 22 kg (49 lb)
- Absolute Uncertainty Definition** The 5502A specifications include stability, temperature coefficient, linearity, line and load regulation, and the traceability of the external standards used for calibration. You do not need to add anything to determine the total specification of the 5502A for the temperature range indicated.
- Specification Confidence Level** 99 %

Detailed Specifications

DC Voltage

| Range | Absolute Uncertainty, tcal $\pm 5\text{ }^\circ\text{C}$ $\pm(\%$ of output + μV) | | Stability | Resolution (μV) | Max Burden ^[1] |
|--|--|---------------|---|------------------------------|---------------------------|
| | 90 Day | 1 Year | 24 hours, $\pm 1\text{ }^\circ\text{C}$ $\pm(\text{ppm}$ of output + μV) | | |
| 0 to 329.9999 mV | 0.005 + 3 | 0.006 + 3 | 5 + 1 | 0.1 | 65 Ω |
| 0 to 3.299999 V | 0.004 + 5 | 0.005 + 5 | 4 + 3 | 1 | 10 mA |
| 0 to 32.999999 V | 0.004 + 50 | 0.005 + 50 | 4 + 30 | 10 | 10 mA |
| 30 to 329.9999 V | 0.0045 + 500 | 0.0055 + 500 | 4.5 + 300 | 100 | 5 mA |
| 100 to 1020.000 V | 0.0045 + 1500 | 0.0055 + 1500 | 4.5 + 900 | 1000 | 5 mA |
| Auxiliary Output (dual output mode only) ^[2] | | | | | |
| 0 to 329.999 mV | 0.03 + 350 | 0.04 + 350 | 30 + 100 | 1 | 5 mA |
| 0.33 to 3.29999 V | 0.03 + 350 | 0.04 + 350 | 30 + 100 | 10 | 5 mA |
| 3.3 to 7 V | 0.03 + 350 | 0.04 + 350 | 30 + 100 | 100 | 5 mA |
| TC Simulate and Measure in Linear 10 $\mu\text{V}/^\circ\text{C}$ and 1 $\text{mV}/^\circ\text{C}$ modes ^[3] | | | | | |
| 0 to 329.9999 mV | 0.005 + 3 | 0.006 + 3 | 5 + 1 | 0.1 | 10 Ω |
| [1] Remote sensing is not provided. Output resistance is $< 5\text{ m}\Omega$ for outputs $\geq 0.33\text{ V}$. The AUX output has an output resistance of $< 1\text{ }\Omega$. TC simulation has an output impedance of $10\text{ }\Omega \pm 1\text{ }\Omega$. [2] Two channels of dc voltage output are provided. [3] TC simulating and measuring are not specified for operation in electromagnetic fields above 0.4 V/m. | | | | | |

| Range | Noise | |
|--|--|-------------------------------|
| | Bandwidth 0.1 Hz to 10 Hz p-p $\pm(\text{ppm}$ of output + floor in μV) | Bandwidth 10 Hz to 10 kHz rms |
| 0 to 329.9999 mV | 0 + 1 | 6 μV |
| 0 to 3.299999 V | 0 + 10 | 60 μV |
| 0 to 32.999999 V | 0 + 100 | 600 μV |
| 30 to 329.9999 V | 10 + 1000 | 20 mV |
| 100 to 1020.000 V | 10 + 5000 | 20 mV |
| Auxiliary Output (dual output mode only) ^[1] | | |
| 0 to 329.999 mV | 0 + 5 μV | 20 μV |
| 0.33 to 3.29999 V | 0 + 20 μV | 200 μV |
| 3.3 to 7 V | 0 + 100 μV | 1000 μV |
| [1] Two channels of dc voltage output are provided. | | |

DC Current

| Range | Absolute Uncertainty, tcal $\pm 5^\circ\text{C}$ $\pm(\%$ of output $+\mu\text{A})$ | | Resolution | Max Compliance Voltage V | Max Inductive Load mH |
|--------------------------------|--|---------------------------|--------------------|--------------------------|-----------------------|
| | 90 Day | 1 Year | | | |
| 0 to 329.999 μA | 0.012 + 0.02 | 0.015 + 0.02 | 1 nA | 10 | 400 |
| 0 to 3.29999 mA | 0.010 + 0.05 | 0.013 + 0.05 | 0.01 μA | 10 | |
| 0 to 32.9999 mA | 0.008 + 0.25 | 0.010 + 0.25 | 0.1 μA | 7 | |
| 0 to 329.999 mA | 0.008 + 3.3 | 0.010 + 2.5 | 1 μA | 7 | |
| 0 to 1.09999 A | 0.023 + 44 | 0.038 + 44 | 10 μA | 6 | |
| 1.1 to 2.99999 A | 0.030 + 44 | 0.038 + 44 | 10 μA | 6 | |
| 0 to 10.9999 A (20 A Range) | 0.038 + 500 | 0.060 + 500 | 100 μA | 4 | |
| 11 to 20.5 A ^[1] | 0.080 + 750 ^[2] | 0.10 + 750 ^[2] | 100 μA | 4 | |

[1] Duty Cycle: Currents <11 A may be provided continuously. For currents >11 A, see Figure 1. The current may be provided Formula $60 - T - I$ minutes any 60 minute period where T is the temperature in $^\circ\text{C}$ (room temperature is about 23°C) and I is the output current in amperes. For example, 17 A, at 23°C could be provided for $60 - 23 - 17 = 20$ minutes each hour. When the 5502A is outputting currents between 5 and 11 amps for long periods, the internal self-heating reduces the duty cycle. Under those conditions, the allowable "on" time indicated by the formula and Figure 1 is achieved only after the 5502A is outputting currents <5 A for the "off" period first.

[2] Floor specification is 1500 μA within 30 seconds of selecting operate. For operating times >30 seconds, the floor specification is 750 μA .

| Range | Noise | |
|----------------------------|-------------------------------|-------------------------------|
| | Bandwidth 0.1 Hz to 10 Hz p-p | Bandwidth 10 Hz to 10 kHz rms |
| 0 to 329.999 μA | 2 nA | 20 nA |
| 0 to 3.29999 mA | 20 nA | 200 nA |
| 0 to 32.9999 mA | 200 nA | 2.0 μA |
| 0 to 329.999 mA | 2000 nA | 20 μA |
| 0 to 2.99999 A | 20 μA | 1 mA |
| 0 to 20.5 A | 200 μA | 10 mA |




Figure 1. Allowable Duration of Current >11 A

Resistance

| Range ^[1] | Absolute Uncertainty, tcal ± 5 °C \pm (% of output + floor) ^[2] | | | | Resolution (Ω) | Allowable Current ^[3] (A) |
|--------------------------------------|--|--------|--|-------------------|-------------------------|--------------------------------------|
| | % of output | | Floor (Ω) Time and temp since ohms zero cal | | | |
| | 90 Day | 1 Year | 12 hrs ± 1 °C | 7 days ± 5 °C | | |
| 0 to 10.999 Ω | 0.009 | 0.012 | 0.001 | 0.01 | 0.001 | 4 mA to 125 mA |
| 11 to 32.999 Ω | 0.009 | 0.012 | 0.0015 | 0.015 | 0.001 | 4 mA to 125 mA |
| 33 to 109.999 Ω | 0.007 | 0.009 | 0.0014 | 0.015 | 0.001 | 3 mA to 70 mA |
| 110 to 329.999 Ω | 0.007 | 0.009 | 0.002 | 0.02 | 0.001 | 1 mA to 40 mA |
| 330 to 1.09999 k Ω | 0.007 | 0.009 | 0.002 | 0.02 | 0.01 | 1 mA to 13.5 mA |
| 1.1 to 3.29999 k Ω | 0.007 | 0.009 | 0.02 | 0.2 | 0.01 | 100 μ A to 4.5 mA |
| 3.3 to 10.9999 k Ω | 0.007 | 0.009 | 0.02 | 0.1 | 0.1 | 100 μ A to 1.35 mA |
| 11 to 32.9999 k Ω | 0.007 | 0.009 | 0.2 | 1 | 0.1 | 10 μ A to 0.45 mA |
| 33 to 109.999 k Ω | 0.008 | 0.011 | 0.2 | 1 | 1 | 10 μ A to 0.135 mA |
| 110 to 329.999 k Ω | 0.009 | 0.012 | 2 | 10 | 1 | 1 μ A to 0.045 μ A |
| 330 k Ω to 1.09999 M Ω | 0.011 | 0.015 | 2 | 10 | 10 | 1 μ A to 0.0135 μ A |
| 1.1 to 3.29999 M Ω | 0.011 | 0.015 | 30 | 150 | 10 | 250 nA to 4.5 μ A |
| 3.3 to 10.9999 M Ω | 0.045 | 0.06 | 50 | 250 | 100 | 250 nA to 1.35 μ A |
| 11 to 32.9999 M Ω | 0.075 | 0.1 | 2500 | 2500 | 100 | 25 nA to 450 nA |
| 33 to 109.999 M Ω | 0.4 | 0.5 | 3000 | 3000 | 1000 | 25 nA to 135 nA |
| 110 to 329.999 M Ω | 0.4 | 0.5 | 100000 | 100000 | 1000 | 2.5 nA to 45 nA |
| 330 to 1100.00 M Ω | 1.2 | 1.5 | 500000 | 500000 | 10000 | 1 nA to 13 nA |

[1] Continuously variable from 0 Ω to 1.1 G Ω .

[2] Applies for 4-WIRE compensation only. For 2-WIRE and 2-WIRE COMP, add 5 μ V per amp of stimulus current to the floor specification. For example, in 2-WIRE mode, at 1 k Ω the floor specification within 12 hours of an ohms zero cal for a measurement current of 1 mA is: $0.002 \Omega + 5 \mu\text{V} / 1 \text{ mA} = (0.002 + 0.005) \Omega = 0.007 \Omega$.

[3] Do not exceed the largest current for each range. For currents lower than shown, the floor adder increases by $\text{Floor}_{(\text{new})} = \text{Floor}_{(\text{old})} \times I_{\text{min}}/I_{\text{actual}}$. For example, a 50 μ A stimulus measuring 100 Ω has a floor specification of: $0.0014 \Omega \times 3 \text{ mA}/50 \mu\text{A} = 0.084 \Omega$, assuming an ohms zero calibration within 12 hours.

AC Voltage (Sine Wave)

| Range | Frequency | Absolute Uncertainty, tcal ±5 °C ± (% of output + μV) | | Resolution | Max Burden | Max Distortion and Noise 10 Hz to 5 MHz Bandwidth ±(% of output + floor) |
|------------------------|--------------------|---|---------------|------------|--|--|
| | | 90 Day | 1 Year | | | |
| 1.0 to 32.999 mV | 10 Hz to 45 Hz | 0.120 + 20 | 0.150 + 20 | 1 μV | 65 Ω | 0.15 + 90 μV |
| | 45 Hz to 10 kHz | 0.080 + 20 | 0.100 + 20 | | | 0.035 + 90 μV |
| | 10 kHz to 20 kHz | 0.120 + 20 | 0.150 + 20 | | | 0.06 + 90 μV |
| | 20 kHz to 50 kHz | 0.160 + 20 | 0.200 + 20 | | | 0.15 + 90 μV |
| | 50 kHz to 100 kHz | 0.300 + 33 | 0.350 + 33 | | | 0.25 + 90 μV |
| | 100 kHz to 500 kHz | 0.750 + 60 | 1.000 + 60 | | | 0.3 + 90 μV ^[1] |
| 33 mV to 329.999 mV | 10 Hz to 45 Hz | 0.042 + 20 | 0.050 + 20 | 1 μV | 65 Ω | 0.15 + 90 μV |
| | 45 Hz to 10 kHz | 0.029 + 20 | 0.030 + 20 | | | 0.035 + 90 μV |
| | 10 kHz to 20 kHz | 0.066 + 20 | 0.070 + 20 | | | 0.06 + 90 μV |
| | 20 kHz to 50 kHz | 0.086 + 40 | 0.100 + 40 | | | 0.15 + 90 μV |
| | 50 kHz to 100 kHz | 0.173 + 170 | 0.230 + 170 | | | 0.2 + 90 μV |
| | 100 kHz to 500 kHz | 0.400 + 330 | 0.500 + 330 | | | 0.2 + 90 μV ^[1] |
| 0.33 V to 3.29999 V | 10 Hz to 45 Hz | 0.042 + 60 | 0.050 + 60 | 10 μV | 10 mA | 0.15 + 200 μV |
| | 45 Hz to 10 kHz | 0.028 + 60 | 0.030 + 60 | | | 0.035 + 200 μV |
| | 10 kHz to 20 kHz | 0.059 + 60 | 0.070 + 60 | | | 0.06 + 200 μV |
| | 20 kHz to 50 kHz | 0.083 + 60 | 0.100 + 60 | | | 0.15 + 200 μV |
| | 50 kHz to 100 kHz | 0.181 + 200 | 0.230 + 200 | | | 0.2 + 200 μV |
| | 100 kHz to 500 kHz | 0.417 + 900 | 0.500 + 900 | | | 0.2 + 200 μV ^[1] |
| 3.3 V to 32.9999 V | 10 Hz to 45 Hz | 0.042 + 800 | 0.050 + 800 | 100 μV | 10 mA | 0.15 + 2 mV |
| | 45 Hz to 10 kHz | 0.025 + 600 | 0.030 + 600 | | | 0.035 + 2 mV |
| | 10 kHz to 20 kHz | 0.064 + 600 | 0.070 + 600 | | | 0.08 + 2 mV |
| | 20 kHz to 50 kHz | 0.086 + 600 | 0.100 + 600 | | | 0.2 + 2 mV |
| | 50 kHz to 100 kHz | 0.192 + 2000 | 0.230 + 2000 | | | 0.5 + 2 mV |
| 33 V to 329.999 V | 45 Hz to 1 kHz | 0.039 + 3000 | 0.050 + 3000 | 1 mV | 5 mA, except 20 mA for 45 Hz to 65 Hz | 0.15 + 10 mV |
| | 1 kHz to 10 kHz | 0.064 + 9000 | 0.080 + 9000 | | | 0.05 + 10 mV |
| | 10 kHz to 20 kHz | 0.079 + 9000 | 0.090 + 9000 | | | 0.6 + 10 mV |
| | 20 kHz to 50 kHz | 0.096 + 9000 | 0.120 + 9000 | | | 0.8 + 10 mV |
| | 50 kHz to 100 kHz | 0.192 + 80000 | 0.240 + 80000 | | | 1 + 10 mV |
| 330 V to 1020 V | 45 Hz to 1 kHz | 0.042 + 20000 | 0.050 + 20000 | 10 mV | 2 mA, except 6 mA for 45 to 65 Hz | 0.15 + 30 mV |
| | 1 kHz to 5 kHz | 0.064 + 20000 | 0.080 + 20000 | | | 0.07 + 30 mV |
| | 5 kHz to 10 kHz | 0.075 + 20000 | 0.090 + 20000 | | | 0.07 + 30 mV |

[1] Max Distortion for 100 kHz to 200 kHz. For 200 kHz to 500 kHz, the maximum distortion is 0.9 % of output + floor as shown.

Note
Remote sensing is not provided. Output resistance is <5 mΩ for outputs ≥0.33 V. The AUX output resistance is <1 Ω. The maximum load capacitance is 500 pF, subject to the maximum burden current limits.

| AUX (Auxiliary Output) [dual output mode only] | | | | | | |
|--|--------------------------|---|-------------|------------|------------|--|
| Range | Frequency ^[1] | Absolute Uncertainty, tcal ±5 °C ±(% of output + μV) | | Resolution | Max Burden | Max Distortion and Noise 10 Hz to 5 MHz Bandwidth ±(% of output + floor) |
| | | 90 Day | 1 Year | | | |
| 1.0 to 329.999 mV | 10 to 20 Hz | 0.15 + 370 | 0.20 + 370 | 1 μV | 5 mA | 0.20 + 200 μV |
| | 20 to 45 Hz | 0.08 + 370 | 0.10 + 370 | | | 0.06 + 200 μV |
| | 45 to 1 kHz | 0.08 + 370 | 0.10 + 370 | | | 0.08 + 200 μV |
| | 1 to 5 kHz | 0.15 + 450 | 0.20 + 450 | | | 0.30 + 200 μV |
| | 5 to 10 kHz | 0.30 + 450 | 0.40 + 450 | | | 0.60 + 200 μV |
| | 10 to 30 kHz | 4.00 + 900 | 5.00 + 900 | | | 1.00 + 200 μV |
| 0.33 to 3.29999 V | 10 to 20 Hz | 0.15 + 450 | 0.20 + 450 | 10 μV | 5 mA | 0.20 + 200 μV |
| | 20 to 45 Hz | 0.08 + 450 | 0.10 + 450 | | | 0.06 + 200 μV |
| | 45 to 1 kHz | 0.07 + 450 | 0.09 + 450 | | | 0.08 + 200 μV |
| | 1 to 5 kHz | 0.15 + 1400 | 0.20 + 1400 | | | 0.30 + 200 μV |
| | 5 to 10 kHz | 0.30 + 1400 | 0.40 + 1400 | | | 0.60 + 200 μV |
| | 10 to 30 kHz | 4.00 + 2800 | 5.00 + 2800 | | | 1.00 + 200 μV |
| 3.3 to 5 V | 10 to 20 Hz | 0.15 + 450 | 0.20 + 450 | 100 μV | 5 mA | 0.20 + 200 μV |
| | 20 to 45 Hz | 0.08 + 450 | 0.10 + 450 | | | 0.06 + 200 μV |
| | 45 to 1 kHz | 0.07 + 450 | 0.09 + 450 | | | 0.08 + 200 μV |
| | 1 to 5 kHz | 0.15 + 1400 | 0.20 + 1400 | | | 0.30 + 200 μV |
| | 5 to 10 kHz | 0.30 + 1400 | 0.40 + 1400 | | | 0.60 + 200 μV |

[1] There are two channels of voltage output. The maximum frequency of the dual output is 30 kHz.

Note

Remote sensing is not provided. Output resistance is <5 mΩ for outputs ≥0.33 V. The AUX output resistance is <1 Ω. The maximum load capacitance is 500 pF, subject to the maximum burden current limits.

AC Current (Sine Wave)

| Range | Frequency | Absolute Uncertainty, tcal ± 5 °C \pm (% of output + μ A) | | Compliance adder $\pm(\mu$ A/V) | Max Distortion and Noise 10 Hz to 100 kHz BW \pm (% of output + floor) | Max Inductive Load μ H |
|---|-----------------|---|--------------|------------------------------------|--|----------------------------------|
| | | 90 Day | 1 Year | | | |
| LCOMP Off | | | | | | |
| 29 to 329.99 μ A | 10 to 20 Hz | 0.16 + 0.1 | 0.2 + 0.1 | 0.05 | 0.15 + 0.5 μ A | 200 |
| | 20 to 45 Hz | 0.12 + 0.1 | 0.15 + 0.1 | 0.05 | 0.10 + 0.5 μ A | |
| | 45 Hz to 1 kHz | 0.1 + 0.1 | 0.125 + 0.1 | 0.05 | 0.05 + 0.5 μ A | |
| | 1 to 5 kHz | 0.25 + 0.15 | 0.3 + 0.15 | 1.5 | 0.50 + 0.5 μ A | |
| | 5 to 10 kHz | 0.6 + 0.2 | 0.8 + 0.2 | 1.5 | 1.00 + 0.5 μ A | |
| 0.33 to 3.29999 mA | 10 to 20 Hz | 0.16 + 0.15 | 0.2 + 0.15 | 0.05 | 0.15 + 1.5 μ A | 200 |
| | 20 to 45 Hz | 0.1 + 0.15 | 0.125 + 0.15 | 0.05 | 0.06 + 1.5 μ A | |
| | 45 Hz to 1 kHz | 0.08 + 0.15 | 0.1 + 0.15 | 0.05 | 0.02 + 1.5 μ A | |
| | 1 to 5 kHz | 0.16 + 0.2 | 0.2 + 0.2 | 1.5 | 0.50 + 1.5 μ A | |
| | 5 to 10 kHz | 0.4 + 0.3 | 0.5 + 0.3 | 1.5 | 1.00 + 1.5 μ A | |
| 3.3 to 32.9999 mA | 10 to 20 Hz | 0.15 + 2 | 0.18 + 2 | 0.05 | 0.15 + 5 μ A | 50 |
| | 20 to 45 Hz | 0.075 + 2 | 0.09 + 2 | 0.05 | 0.05 + 5 μ A | |
| | 45 Hz to 1 kHz | 0.035 + 2 | 0.04 + 2 | 0.05 | 0.07 + 5 μ A | |
| | 1 to 5 kHz | 0.065 + 2 | 0.08 + 2 | 1.5 | 0.30 + 5 μ A | |
| | 5 to 10 kHz | 0.16 + 3 | 0.2 + 3 | 1.5 | 0.70 + 5 μ A | |
| 33 to 329.999 mA | 10 to 20 Hz | 0.15 + 20 | 0.18 + 20 | 0.05 | 0.15 + 50 μ A | 50 |
| | 20 to 45 Hz | 0.075 + 20 | 0.09 + 20 | 0.05 | 0.05 + 50 μ A | |
| | 45 Hz to 1 kHz | 0.035 + 20 | 0.04 + 20 | 0.05 | 0.02 + 50 μ A | |
| | 1 to 5 kHz | 0.08 + 50 | 0.10 + 50 | 1.5 | 0.03 + 50 μ A | |
| | 5 to 10 kHz | 0.16 + 100 | 0.2 + 100 | 1.5 | 0.10 + 50 μ A | |
| 0.33 to 1.09999 A | 10 to 45 Hz | 0.15 + 100 | 0.18 + 100 | | 0.20 + 500 μ A | 2.5 |
| | 45 Hz to 1 kHz | 0.036 + 100 | 0.05 + 100 | | 0.07 + 500 μ A | |
| | 1 to 5 kHz | 0.5 + 1000 | 0.6 + 1000 | [2] | 1.00 + 500 μ A | |
| | 5 to 10 kHz | 2.0 + 5000 | 2.5 + 5000 | [3] | 2.00 + 500 μ A | |
| 1.1 to 2.99999 A | 10 to 45 Hz | 0.15 + 100 | 0.18 + 100 | | 0.20 + 500 μ A | 2.5 |
| | 45 Hz to 1 kHz | 0.05 + 100 | 0.06 + 100 | | 0.07 + 500 μ A | |
| | 1 to 5 kHz | 0.5 + 1000 | 0.6 + 1000 | [2] | 1.00 + 500 μ A | |
| | 5 to 10 kHz | 2.0 + 5000 | 2.5 + 5000 | [3] | 2.00 + 500 μ A | |
| 3 to 10.9999 A | 45 to 100 Hz | 0.05 + 2000 | 0.06 + 2000 | | 0.2 + 3 mA | 1 |
| | 100 Hz to 1 kHz | 0.08 + 2000 | 0.10 + 2000 | | 0.1 + 3 mA | |
| | 1 kHz to 5 kHz | 2.5 + 2000 | 3.0 + 2000 | | 0.8 + 3 mA | |
| 11 to 20.5 A ^[1] | 45 to 100 Hz | 0.1 + 5000 | 0.12 + 5000 | | 0.2 + 3 mA | 1 |
| | 100 Hz to 1 kHz | 0.13 + 5000 | 0.15 + 5000 | | 0.1 + 3 mA | |
| | 1 to 5 kHz | 2.5 + 5000 | 3.0 + 5000 | | 0.8 + 3 mA | |
| <p>[1] Duty Cycle: Currents <11 A may be provided continuously. For currents >11 A, see Figure 1. The current may be provided 60-T-I minutes any 60 minute period where T is the temperature in °C (room temperature is about 23 °C) and I is the output current in amps. For example, 17 A, at 23 °C could be provided for 60-17-23 = 20 minutes each hour. When the 5502A is outputting currents between 5 and 11 amps for long periods, the internal self-heating reduces the duty cycle. Under those conditions, the allowable "on" time indicated by the formula and Figure 1 is achieved only after the 5502A is outputting currents <5 A for the "off" period first.</p> <p>[2] For compliance voltages greater than 1 V, add 1 mA/V to the floor specification from 1 to 5 kHz.</p> <p>[3] For compliance voltages greater than 1 V, add 5 mA/V to the floor specification from 5 to 10 kHz.</p> | | | | | | |

AC Current (Sine Wave) (cont.)

| Range | Frequency | Absolute Uncertainty, tc1 ±5 °C ±(% of output + µA) | | Max Distortion and Noise 10 Hz to 100 kHz BW ±(% of output + floor) | Max Inductive Load |
|---|-----------------|--|----------------------------|--|-----------------------|
| | | 90 Day | 1 Year | | |
| LCOMP On | | | | | |
| 29 to 329.99 µA | 10 to 100 Hz | 0.20 + 0.2 | 0.25 + 0.2 | 0.1 + 1.0 µA | 400 µH |
| | 100 Hz to 1 kHz | 0.50 + 0.5 | 0.60 + 0.5 | 0.05 + 1.0 µA | |
| 330 µA to 3.29999 mA | 10 to 100 Hz | 0.20 + 0.3 | 0.25 + 0.3 | 0.15 + 1.5 µA | |
| | 100 Hz to 1 kHz | 0.50 + 0.8 | 0.60 + 0.8 | 0.06 + 1.5 µA | |
| 3.3 to 32.9999 mA | 10 to 100 Hz | 0.07 + 4 | 0.08 + 4 | 0.15 + 5 µA | |
| | 100 Hz to 1 kHz | 0.18 + 10 | 0.20 + 10 | 0.05 + 5 µA | |
| 33 to 329.999 mA | 10 to 100 Hz | 0.07 + 40 | 0.08 + 40 | 0.15 + 50 µA | |
| | 100 Hz to 1 kHz | 0.18 + 100 | 0.20 + 100 | 0.05 + 50 µA | |
| 330 mA to 2.99999 A | 10 to 100 Hz | 0.10 + 200 | 0.12 + 200 | 0.2 + 500 µA | |
| | 100 to 440 Hz | 0.25 + 1000 | 0.30 + 1000 | 0.25 + 500 µA | |
| 3.3 A to 20.5 A ^[1] | 45 to 100 Hz | 0.10 + 2000 ^[2] | 0.12 + 2000 ^[2] | 0.1 + 0 µA | 400 µH ^[4] |
| | 100 to 440 Hz | 0.80 + 5000 ^[3] | 1.00 + 5000 ^[3] | 0.5 + 0 µA | |
| <p>[1] Duty Cycle: Currents <11 A may be provided continuously. For currents >11 A, see Figure 1. The current may be provided 60-T-I minutes any 60 minute period where T is the temperature in °C (room temperature is about 23 °C) and I is the output current in amps. For example, 17 A, at 23 °C could be provided for 60-17-23 = 20 minutes each hour. When the 5502A is outputting currents between 5 and 11 amps for long periods, the internal self-heating reduces the duty cycle. Under those conditions, the allowable "on" time indicated by the formula and Figure 1 is achieved only after the 5502A is outputting currents <5 A for the "off" period first.</p> <p>[2] For currents >11 A, Floor specification is 4000 µA within 30 seconds of selecting operate. For operating times >30 seconds, the floor specification is 2000 µA.</p> <p>[3] For currents >11 A, Floor specification is 10000 µA within 30 seconds of selecting operate. For operating times >30 seconds, the floor specification is 5000 µA.</p> <p>[4] Subject to compliance voltages limits.</p> | | | | | |

| Range | Resolution µA | Max Compliance Voltage V rms ^[1] |
|--|---------------|---|
| 29 to 329.99 µA | 0.01 | 7 |
| 0.33 to 3.29999 mA | 0.01 | 7 |
| 3.3 to 32.9999 mA | 0.1 | 5 |
| 33 to 329.999 mA | 1 | 5 |
| 0.33 to 2.99999 A | 10 | 4 |
| 3 to 20.5 A | 100 | 3 |
| [1] Subject to specification adder for compliance voltages greater than 1 V rms. | | |

Capacitance

| Range | Absolute Uncertainty, tcal ± 5 °C $\pm(\% \text{ of output} + \text{floor})$ [1] [2] [3] | | Resolution | Allowed Frequency or Charge-Discharge Rate | | |
|------------------------|---|-------------------|------------|--|------------------------------|----------------------------|
| | 90 Day | 1 Year | | Min and Max to Meet Specification | Typical Max for <0.5 % Error | Typical Max for <1 % Error |
| 220.0 to 399.9 pF | 0.38 + 0.01 nF | 0.5 + 0.01 nF | 0.1 pF | 10 Hz to 10 kHz | 20 kHz | 40 kHz |
| 0.4 to 1.0999 nF | 0.38 + 0.01 nF | 0.5 + 0.01 nF | 0.1 pF | 10 Hz to 10 kHz | 30 kHz | 50 kHz |
| 1.1 to 3.2999 nF | 0.38 + 0.01 nF | 0.5 + 0.01 nF | 0.1 pF | 10 Hz to 3 kHz | 30 kHz | 50 kHz |
| 3.3 to 10.999 nF | 0.19 + 0.01 nF | 0.25 + 0.01 nF | 1 pF | 10 Hz to 1 kHz | 20 kHz | 25 kHz |
| 11 to 32.999 nF | 0.19 + 0.1 nF | 0.25 + 0.1 nF | 1 pF | 10 Hz to 1 kHz | 8 kHz | 10 kHz |
| 33 to 109.99 nF | 0.19 + 0.1 nF | 0.25 + 0.1 nF | 10 pF | 10 Hz to 1 kHz | 4 kHz | 6 kHz |
| 110 to 329.99 nF | 0.19 + 0.3 nF | 0.25 + 0.3 nF | 10 pF | 10 Hz to 1 kHz | 2.5 kHz | 3.5 kHz |
| 0.33 to 1.0999 μ F | 0.19 + 1 nF | 0.25 + 1 nF | 100 pF | 10 to 600 Hz | 1.5 kHz | 2 kHz |
| 1.1 to 3.2999 μ F | 0.19 + 3 nF | 0.25 + 3 nF | 100 pF | 10 to 300 Hz | 800 Hz | 1 kHz |
| 3.3 to 10.999 μ F | 0.19 + 10 nF | 0.25 + 10 nF | 1 nF | 10 to 150 Hz | 450 Hz | 650 Hz |
| 11 to 32.999 μ F | 0.30 + 30 nF | 0.40 + 30 nF | 1 nF | 10 to 120 Hz | 250 Hz | 350 Hz |
| 33 to 109.99 μ F | 0.34 + 100 nF | 0.45 + 100 nF | 10 nF | 10 to 80 Hz | 150 Hz | 200 Hz |
| 110 to 329.99 μ F | 0.34 + 300 nF | 0.45 + 300 nF | 10 nF | 0 to 50 Hz | 80 Hz | 120 Hz |
| 0.33 to 1.0999 mF | 0.34 + 1 μ F | 0.45 + 1 μ F | 100 nF | 0 to 20 Hz | 45 Hz | 65 Hz |
| 1.1 to 3.2999 mF | 0.34 + 3 μ F | 0.45 + 3 μ F | 100 nF | 0 to 6 Hz | 30 Hz | 40 Hz |
| 3.3 to 10.999 mF | 0.34 + 10 μ F | 0.45 + 10 μ F | 1 μ F | 0 to 2 Hz | 15 Hz | 20 Hz |
| 11 to 32.999 mF | 0.7 + 30 μ F | 0.75 + 30 μ F | 1 μ F | 0 to 0.6 Hz | 7.5 Hz | 10 Hz |
| 33 to 110.00 mF | 1.0 + 100 μ F | 1.1 + 100 μ F | 10 μ F | 0 to 0.2 Hz | 3 Hz | 5 Hz |

[1] The output is continuously variable from 220 pF to 110 mF.

[2] Specifications apply to both dc charge/discharge capacitance meters and ac RCL meters. The maximum allowable peak voltage is 3 V. The maximum allowable peak current is 150 mA, with an rms limitation of 30 mA below 1.1 μ F and 100 mA for 1.1 μ F and above.

[3] The maximum lead resistance for no additional error in 2-wire COMP mode is 10 Ω .

Temperature Calibration (Thermocouple)

| TC Type [1] | Range °C [2] | Absolute Uncertainty Source/Measure tcal ±5 °C ± °C [3] | | TC Type [1] | Range °C [2] | Absolute Uncertainty Source/Measure tcal ±5 °C ± °C [3] | |
|----------------|--------------|---|-----------|-------------------|--------------|---|--------|
| | | 90 Day | 1 Year | | | 90 Day | 1 Year |
| B | 600 to 800 | 0.42 | 0.44 | L | -200 to -100 | 0.37 | 0.37 |
| | 800 to 1000 | 0.34 | 0.34 | | -100 to 800 | 0.26 | 0.26 |
| | 1000 to 1550 | 0.30 | 0.30 | | 800 to 900 | 0.17 | 0.17 |
| | 1550 to 1820 | 0.26 | 0.33 | | | | |
| C | 0 to 150 | 0.23 | 0.30 | N | -200 to -100 | 0.30 | 0.40 |
| | 150 to 650 | 0.19 | 0.26 | | -100 to -25 | 0.17 | 0.22 |
| | 650 to 1000 | 0.23 | 0.31 | | -25 to 120 | 0.15 | 0.19 |
| | 1000 to 1800 | 0.38 | 0.50 | | 120 to 410 | 0.14 | 0.18 |
| | 1800 to 2316 | 0.63 | 0.84 | | 410 to 1300 | 0.21 | 0.27 |
| E | -250 to -100 | 0.38 | 0.50 | R | 0 to 250 | 0.48 | 0.57 |
| | -100 to -25 | 0.12 | 0.16 | | 250 to 400 | 0.28 | 0.35 |
| | -25 to 350 | 0.10 | 0.14 | | 400 to 1000 | 0.26 | 0.33 |
| | 350 to 650 | 0.12 | 0.16 | | 1000 to 1767 | 0.30 | 0.40 |
| | 650 to 1000 | 0.16 | 0.21 | S | 0 to 250 | 0.47 | 0.47 |
| J | -210 to -100 | 0.20 | 0.27 | | 250 to 1000 | 0.30 | 0.36 |
| | -100 to -30 | 0.12 | 0.16 | | 1000 to 1400 | 0.28 | 0.37 |
| | -30 to 150 | 0.10 | 0.14 | 1400 to 1767 | 0.34 | 0.46 | |
| | 150 to 760 | 0.13 | 0.17 | T | -250 to -150 | 0.48 | 0.63 |
| 760 to 1200 | 0.18 | 0.23 | -150 to 0 | | 0.18 | 0.24 | |
| K | -200 to -100 | 0.25 | 0.33 | | 0 to 120 | 0.12 | 0.16 |
| | -100 to -25 | 0.14 | 0.18 | | 120 to 400 | 0.10 | 0.14 |
| | -25 to 120 | 0.12 | 0.16 | U | -200 to 0 | 0.56 | 0.56 |
| | 120 to 1000 | 0.19 | 0.26 | | 0 to 600 | 0.27 | 0.27 |
| | 1000 to 1372 | 0.30 | 0.40 | | | | |
| | | | | | | | |

[1] Temperature standard ITS-90 or IPTS-68 is selectable.
TC simulating and measuring are not specified for operation in electromagnetic fields above 0.4 V/m.

[2] Resolution is 0.01 °C

[3] Does not include thermocouple error

Temperature Calibration (RTD)

| RTD Type | Range °C ^[1] | Absolute Uncertainty tcal ±5 °C ± °C ^[2] | | RTD Type | Range °C ^[1] | Absolute Uncertainty tcal ±5 °C ± °C ^[2] | |
|-------------------|-------------------------|--|--------|-------------------------------|-------------------------|--|--------|
| | | 90 Day | 1 Year | | | 90 Day | 1 Year |
| Pt 385, 100 Ω | -200 to -80 | 0.04 | 0.05 | Pt 385, 500 Ω | -200 to -80 | 0.03 | 0.04 |
| | -80 to 0 | 0.05 | 0.05 | | -80 to 0 | 0.04 | 0.05 |
| | 0 to 100 | 0.07 | 0.07 | | 0 to 100 | 0.05 | 0.05 |
| | 100 to 300 | 0.08 | 0.09 | | 100 to 260 | 0.06 | 0.06 |
| | 300 to 400 | 0.09 | 0.10 | | 260 to 300 | 0.07 | 0.08 |
| | 400 to 630 | 0.10 | 0.12 | | 300 to 400 | 0.07 | 0.08 |
| | 630 to 800 | 0.21 | 0.23 | | 400 to 600 | 0.08 | 0.09 |
| Pt 3926, 100 Ω | -200 to -80 | 0.04 | 0.05 | Pt 385, 1000 Ω | 600 to 630 | 0.09 | 0.11 |
| | -80 to 0 | 0.05 | 0.05 | | -200 to -80 | 0.03 | 0.03 |
| | 0 to 100 | 0.07 | 0.07 | | -80 to 0 | 0.03 | 0.03 |
| | 100 to 300 | 0.08 | 0.09 | | 0 to 100 | 0.03 | 0.04 |
| | 300 to 400 | 0.09 | 0.10 | | 100 to 260 | 0.04 | 0.05 |
| Pt 3916, 100 Ω | 400 to 630 | 0.10 | 0.12 | PtNi 385, 120 Ω (Ni120) | 260 to 300 | 0.05 | 0.06 |
| | -200 to -190 | 0.25 | 0.25 | | 300 to 400 | 0.05 | 0.07 |
| | -190 to -80 | 0.04 | 0.04 | | 400 to 600 | 0.06 | 0.07 |
| | -80 to 0 | 0.05 | 0.05 | 600 to 630 | 0.22 | 0.23 | |
| | 0 to 100 | 0.06 | 0.06 | Cu 427 10 Ω ^[3] | -80 to 0 | 0.06 | 0.08 |
| | 100 to 260 | 0.06 | 0.07 | | 0 to 100 | 0.07 | 0.08 |
| | 260 to 300 | 0.07 | 0.08 | | 100 to 260 | 0.13 | 0.14 |
| 300 to 400 | 0.08 | 0.09 | | | | | |
| 400 to 600 | 0.08 | 0.10 | | | | | |
| 600 to 630 | 0.21 | 0.23 | | | | | |
| Pt 385, 200 Ω | -200 to -80 | 0.03 | 0.04 | | | | |
| | -80 to 0 | 0.03 | 0.04 | | | | |
| | 0 to 100 | 0.04 | 0.04 | | | | |
| | 100 to 260 | 0.04 | 0.05 | | | | |
| | 260 to 300 | 0.11 | 0.12 | | | | |
| | 300 to 400 | 0.12 | 0.13 | | | | |
| | 400 to 600 | 0.12 | 0.14 | | | | |
| 600 to 630 | 0.14 | 0.16 | | | | | |

[1] Resolution is 0.003 °C

[2] Applies for COMP OFF (to the 5502A Calibrator front panel NORMAL terminals) and 2-wire and 4-wire compensation.

[3] Based on MINCO Application Aid No. 18

Phase

| 1-Year Absolute Uncertainty, tcal ±5 °C, (Δ Φ °) | | | | | |
|--|--------------|-----------------|------------|-------------|--------------|
| Frequency (Hz) | | | | | |
| 10 to 65 Hz | 65 to 500 Hz | 500 Hz to 1 kHz | 1 to 5 kHz | 5 to 10 kHz | 10 to 30 kHz |
| 0.15 ° | 0.9 ° | 2 ° | 6 ° | 10 ° | 15 ° |
| Note See Power and Dual Output Limit Specifications for applicable outputs. | | | | | |

| Phase (Φ) Watts | Phase (Φ) VARs | PF | Power Uncertainty Adder due to Phase Error | | | | | |
|--------------------|-------------------|-------|--|--------------|-----------------|------------|-------------|--------------|
| | | | 10 to 65 Hz | 65 to 500 Hz | 500 Hz to 1 kHz | 1 to 5 kHz | 5 to 10 kHz | 10 to 30 kHz |
| 0 ° | 90 ° | 1.0 | 0.00 % | 0.01 % | 0.06 % | 0.55 % | 1.52 % | 3.41 % |
| 5 ° | 85 ° | 0.996 | 0.02 % | 0.15 % | 0.37 % | 1.46 % | 3.04 % | 5.67 % |
| 10 ° | 80 ° | 0.985 | 0.05 % | 0.29 % | 0.68 % | 2.39 % | 4.58 % | 7.97 % |
| 15 ° | 75 ° | 0.966 | 0.07 % | 0.43 % | 1.00 % | 3.35 % | 6.17 % | 10.34 % |
| 20 ° | 70 ° | 0.940 | 0.10 % | 0.58 % | 1.33 % | 4.35 % | 7.84 % | 12.83 % |
| 25 ° | 65 ° | 0.906 | 0.12 % | 0.74 % | 1.69 % | 5.42 % | 9.62 % | 15.48 % |
| 30 ° | 60 ° | 0.866 | 0.15 % | 0.92 % | 2.08 % | 6.58 % | 11.54 % | 18.35 % |
| 35 ° | 55 ° | 0.819 | 0.18 % | 1.11 % | 2.50 % | 7.87 % | 13.68 % | 21.53 % |
| 40 ° | 50 ° | 0.766 | 0.22 % | 1.33 % | 2.99 % | 9.32 % | 16.09 % | 25.12 % |
| 45 ° | 45 ° | 0.707 | 0.26 % | 1.58 % | 3.55 % | 11.00 % | 18.88 % | 29.29 % |
| 50 ° | 40 ° | 0.643 | 0.31 % | 1.88 % | 4.22 % | 13.01 % | 22.21 % | 34.25 % |
| 55 ° | 35 ° | 0.574 | 0.37 % | 2.26 % | 5.05 % | 15.48 % | 26.32 % | 40.37 % |
| 60 ° | 30 ° | 0.500 | 0.45 % | 2.73 % | 6.11 % | 18.65 % | 31.60 % | 48.24 % |
| 65 ° | 25 ° | 0.423 | 0.56 % | 3.38 % | 7.55 % | 22.96 % | 38.76 % | 58.91 % |
| 70 ° | 20 ° | 0.342 | 0.72 % | 4.33 % | 9.65 % | 29.27 % | 49.23 % | 74.52 % |
| 75 ° | 15 ° | 0.259 | 0.98 % | 5.87 % | 13.09 % | 39.56 % | 66.33 % | 100.00 % |
| 80 ° | 10 ° | 0.174 | 1.49 % | 8.92 % | 19.85 % | 59.83 % | 100.00 % | — |
| 85 ° | 5 ° | 0.087 | 2.99 % | 17.97 % | 39.95 % | — | — | — |
| 90 ° | 0 ° | 0.000 | — | — | — | — | — | — |

To calculate exact ac watts power adders due to phase uncertainty for values not shown, use the subsequent formula:

$$Adder(\%) = 100 \left(1 - \frac{\cos(\Phi + \Delta\Phi)}{\cos(\Phi)} \right)$$

For example: For a PF of .9205 (Φ = 23) and a phase uncertainty of ΔΦ = 0.15, the ac watts power adder is:

$$Adder(\%) = 100 \left(1 - \frac{\cos(23 + .15)}{\cos(23)} \right) = 0.11\%$$

AC and DC Power Specifications

Power is simulated through the controlled simultaneous outputs of voltage and current from the Calibrator. While the amplitude and frequency ranges of the outputs are broad, there are certain combinations of voltage and current where the specifications are valid. In general these are for all dc voltages and currents, and AC voltages of 30 mV to 1020 V, ac currents from 33 mA to 20.5 A, for frequencies from 10 Hz to 30 kHz. Operation outside of these areas, within the overall calibrator capabilities, is possible, but it is not specified. The table and figure below illustrate the specified areas where power and dual output are possible.

Specification Limits for Power and Dual Output Operation

| Frequency | Voltages (NORMAL) | Currents | Voltages (AUX) | Power Factor (PF) |
|-----------------|--------------------|---------------------|------------------|-------------------|
| dc | 0 to ±1020 V | 0 to ±20.5 A | 0 to ±7 V | — |
| 10 to 45 Hz | 33 mV to 32.9999 V | 3.3 mA to 2.99999 A | 10 mV to 5 V | 0 to 1 |
| 45 to 65 Hz | 33 mV to 1020 V | 3.3 mA to 20.5 A | 10 mV to 5 V | 0 to 1 |
| 65 to 500 Hz | 330 mV to 1020 V | 33 mA to 2.99999 A | 100 mV to 5 V | 0 to 1 |
| 65 to 500 Hz | 3.3 to 1020 V | 33 mA to 20.5 A | 100 mV to 5 V | 0 to 1 |
| 500 Hz to 1 kHz | 330 mV to 1020 V | 33 mA to 20.5 A | 100 mV to 5 V | 0 to 1 |
| 1 to 5 kHz | 3.3 to 500 V | 33 mA to 2.99999 A | 100 mV to 5 V | 0 to 1 |
| 5 to 10 kHz | 3.3 to 250 V | 33 to 329.99 mA | 1 to 5 V | 0 to 1 |
| 10 to 30 kHz | 3.3 V to 250 V | 33 mA to 329.99 mA | 1 V to 3.29999 V | 0 to 1 |

Notes

The range of voltages and currents shown in "DC Voltage Specifications," "DC Current Specifications," "AC Voltage (Sine Wave) Specifications," and "AC Current (Sine Wave) Specifications" are available in the power and dual output modes (except minimum current for ac power is 0.33 mA). Only those limits shown in this table and illustrated in the following figure are specified.

See "Calculate Power Uncertainty" to determine the uncertainty at these points.

The phase adjustment range for dual ac outputs is 0 ° to ±179.99 °. The phase resolution for dual ac outputs is 0.01 °.




Figure 2. Permissible Combinations of AC Voltage and AC Current for Power and Dual Output

Calculate the Uncertainty Specifications of Power and Dual Output Settings

Overall uncertainty for power output in watts (or VARs) is based on the root sum square (rss) of the individual uncertainties in percent for the selected voltage, current, and, if AC power, the phase parameters:

$$\text{Watts uncertainty } U_{\text{Power}} = \sqrt{U^2_{\text{Voltage}} + U^2_{\text{Current}} + U^2_{\text{Phase}}}$$

$$\text{VARs uncertainty } U_{\text{VARs}} = \sqrt{U^2_{\text{Voltage}} + U^2_{\text{Current}} + U^2_{\text{Phase}}}$$

$$\text{Dual Output uncertainty } U_{\text{Dual}} = \sqrt{U^2_{\text{Voltage}} + U^2_{\text{AuxVoltage}} + U^2_{\text{Phase}}}$$

Because there are an infinite number of combinations, you must calculate the actual ac power uncertainty for your selected parameters. The results of this method of calculation are shown in the subsequent example. These examples are at various selected calibrator settings (with 1-year specifications):

Examples of Specified Power Uncertainties at Various Output Settings:

| Selected Output Settings | | | | | | Absolute Uncertainty as specified for tcal ±5 °C, ±(% of output setting) | | | Power Absolute Uncertainty ±(% of Watts) ^[1] |
|--------------------------|------------------------|--------------|-----------------------------|-------------------------|------------------------|--|----------------------|--------------------|---|
| Voltage Setting (Volts) | Current Setting (Amps) | Frequency Hz | Phase Setting (units of PF) | Phase Setting (Degrees) | Selected Power (Watts) | U _{Voltage} | U _{Current} | U _{Phase} | U _{Power} |
| +10.000 | +0.500.000 | DC | | | 5 | 0.00550 % | 0.04680 % | | 0.047 % |
| 15.000 | +2.0000 | DC | | | 30 | 0.00533 % | 0.03220 % | | 0.033 % |
| 100.000 | +20.000 | DC | | | 2000 | 0.00600 % | 0.10375 % | | 0.104 % |
| 1000.00 | 20.000 | DC | | | 20000 | 0.00565 % | 0.10375 % | | 0.104 % |
| 120.000 | 1.00000 | 60 | 1 | 0.0 | 120 | 0.05250 % | 0.06000 % | 0.000 % | 0.080 % |
| 120.000 | 1.00000 | 60 | 0.766 | 40.0 | 91.92 | 0.05250 % | 0.06000 % | 0.220 % | 0.234 % |
| 240.000 | 1.00000 | 50 | 1 | 0.0 | 240 | 0.05125 % | 0.06000 % | 0.000 % | 0.079 % |
| 240.000 | 1.00000 | 50 | 0.766 | 40.0 | 183.84 | 0.05125 % | 0.06000 % | 0.220 % | 0.234 % |
| 1000.00 | 20 | 55 | 1 | 0.0 | 20000 | 0.05200 % | 0.14500 % | 0.000 % | 0.154 % |
| 1000.00 | 20 | 55 | 0.766 | 40.0 | 15320 | 0.05200 % | 0.14500 % | 0.220 % | 0.269 % |
| 1000.00 | 20 | 55 | -0.906 | -25.0 | 18120 | 0.05200 % | 0.14500 % | 0.122 % | 0.196 % |
| 100 | 0.30 | 30000 | 1 | 0.0 | 30.0 | 0.12900 % | 0.4667 % | 3.407 % | 3.442 % |
| 100 | 0.30 | 30000 | 0.766 | 40.0 | 22.98 | 0.12900 % | 0.4667 % | 25.128 % | 25.133 % |

[1] Add 0.02 % unless a settling time of 30 seconds is allowed for output currents >10 A or for currents on the highest two current ranges within 30 seconds of an output current >10 A.

Calculate Power Uncertainty

Overall uncertainty for power output in watts (or VARs) is based on the root sum square (RSS) of the individual uncertainties in percent for the selected voltage, current, and phase parameters:

$$\text{Watts uncertainty } U_{\text{Power}} = \sqrt{U^2_{\text{Voltage}} + U^2_{\text{Current}} + U^2_{\text{Phase}}}$$

$$\text{VARs uncertainty } U_{\text{VARs}} = \sqrt{U^2_{\text{Voltage}} + U^2_{\text{Current}} + U^2_{\text{Phase}}}$$

Because there are an infinite number of combinations, you must calculate the actual ac power uncertainty for your selected parameters. The method of calculation is best shown in the subsequent examples (with 1-year specifications):

Example 1 Output: 100 V, 1 A, 60 Hz, Power Factor = 1.0 (Φ=0).

Voltage Uncertainty Uncertainty for 100 V at 60 Hz is 0.050 % + 3 mV, totaling: 100 V x .0005 = 50 mV added to 3 mV = 53 mV. Expressed in percent: 53 mV/100 V x 100 = 0.053 % (see "AC Voltage (Sine Wave) Specifications").

Current Uncertainty Uncertainty for 1 A at 60 Hz is 0.05 % +100 μA, totaling: 1 A x 0.0005 = 500 μA added to 100 μA = 0.6 mA. Expressed in percent: 0.6 mA/1 A x 100 = 0.06 % (see "AC Current (Sine Waves) Specifications").

Phase Uncertainty (Watts) Adder for PF = 1 (Φ=0) at 60 Hz is 0 % (see "Phase Specifications").

Total Power Uncertainty = $U_{\text{power}} = \sqrt{0.053^2 + 0.06^2 + 0^2} = 0.080\%$

Example 2 Output: 100 V, 1 A, 400 Hz, Power Factor = 0.5 ($\Phi=60$)

Voltage Uncertainty Uncertainty for 100 V at 400 Hz is 0.050% + 3 mV, totaling: 100 V x .00005 = 50 mV added to 3 mV = 53 mV. Expressed in percent: 53 mV/100 V x 100 = 0.053 % (see "AC Voltage (Sine Wave) Specifications").

Current Uncertainty Uncertainty for 1 A at 400 Hz is 0.05 % +100 μ A, totaling: 1 A x 0.0005 = 500 μ A added to 100 μ A = 0.6 mA. Expressed in percent: 0.6 mA/1 A x 100 = 0.06 % (see "AC Current (Sine Waves) Specifications").

Phase Uncertainty (Watts) Adder for PF = 0.5 ($\Phi=60$) at 400 Hz is 2.73 % (see "Phase Specifications").

Total Power Uncertainty = $U_{\text{power}} = \sqrt{0.053^2 + 0.06^2 + 2.73^2} = 2.73\%$

VARs When the Power Factor approaches 0.0, the Watts output uncertainty becomes unrealistic because the dominant characteristic is the VARs (volts-amps-reactive) output. In these cases, calculate the Total VARs Output Uncertainty, as shown in example 3:

Example 3 Output: 100 V, 1 A, 60 Hz, Power Factor = 0.174 ($\Phi=80$)

Voltage Uncertainty Uncertainty for 100 V at 60 Hz is 0.050% + 3 mV, totaling: 100 V x .00005 = 50 mV added to 3 mV = 53 mV. Expressed in percent: 53 mV/100 V x 100 = 0.053 % (see "AC Voltage (Sine Wave) Specifications").

Current Uncertainty Uncertainty for 1 A at 60 Hz is 0.05 % +100 μ A, totaling: 1 A x 0.0005 = 500 μ A added to 100 μ A = 0.6 mA. Expressed in percent: 0.6 mA/1 A x 100 = 0.06 % (see "AC Current (Sine Waves) Specifications").

Phase Uncertainty (VARs) Adder for $\Phi=80$ at 60 Hz is 0.05 % (see "Phase Specifications").

Total VARs Uncertainty = $U_{\text{VARs}} = \sqrt{0.053^2 + 0.06^2 + 0.05^2} = 0.094\%$

Additional Specifications

The subsequent paragraphs provide additional specifications for the 5502A Calibrator ac voltage and ac current functions. These specifications are valid after allowing a warm-up period of 30 minutes, or twice the time the 5502A has been turned off. All extended range specifications are based on performing the internal zero-cal function at weekly intervals, or when the ambient temperature changes by more than 5 °C.

Frequency

| Frequency Range | Resolution | 1-Year Absolute Uncertainty, tcal ± 5 °C \pm (ppm + mHz) | Jitter |
|---------------------|------------|--|-----------|
| 0.01 to 119.99 Hz | 0.01 Hz | 25 + 1 | 2 μ s |
| 120.0 to 1199.9 Hz | 0.1 Hz | 25 + 1 | 2 μ s |
| 1.2 to 11.999 kHz | 1 Hz | 25 + 1 | 2 μ s |
| 12 to 119.99 kHz | 10 Hz | 25 + 15 | 140 ns |
| 120.0 to 1199.9 kHz | 100 Hz | 25 + 15 | 140 ns |
| 1.2 to 2.000 MHz | 1 kHz | 25 + 15 | 140 ns |

Harmonics (2nd to 50th)

| Fundamental Frequency ^[1] | Voltages NORMAL Terminals | Currents | Voltages AUX Terminals | Amplitude Uncertainty |
|--------------------------------------|---------------------------|---------------------|------------------------|--|
| 10 to 45 Hz | 33 mV to 32.9999 V | 3.3 mA to 2.99999 A | 10 mV to 5 V | Same % of output as the equivalent single output, but twice the floor adder. |
| 45 to 65 Hz | 33 mV to 1020 V | 3.3 mA to 20.5 A | 10 mV to 5 V | |
| 65 to 500 Hz | 33 mV to 1020 V | 33 mA to 20.5 A | 100 mV to 5 V | |
| 500 Hz to 5 kHz | 330 mV to 1020 V | 33 mA to 20.5 A | 100 mV to 5 V | |
| 5 to 10 kHz | 3.3 to 1020 V | 33 to 329.9999 mA | 100 mV to 5 V | |
| 10 to 30 kHz | 3.3 to 1020 V | 33 to 329.9999 mA | 100 mV to 3.29999 V | |

[1] The maximum frequency of the harmonic output is 30 kHz (10 kHz for 3.3 to 5 V on the Aux terminals). For example, if the fundamental output is 5 kHz, the maximum selection is the 6th harmonic (30 kHz). All harmonic frequencies (2nd to 50th) are available for fundamental outputs between 10 Hz and 600 Hz (200 Hz for 3.3 to 5 V on the Aux terminals).

Phase Uncertainty Phase uncertainty for harmonic outputs is 1 degree or the phase uncertainty shown in "Phase Specifications" for the particular output, whichever is greater. For example, the phase uncertainty of a 400 Hz fundamental output and 10 kHz harmonic output is 10 ° (from "Phase Specifications"). Another example, the phase uncertainty of a 50 Hz fundamental output and a 400 Hz harmonic output is 1 degree.

Example of determining Amplitude Uncertainty in a Dual Output Harmonic Mode

What are the amplitude uncertainties for the following dual outputs?

NORMAL (Fundamental) Output:

100 V, 100 Hz From "AC Voltage (Sine Wave) 90 Day Specifications" the single output specification for 100 V, 100 Hz, is 0.039 % + 3 mV. For the dual output in this example, the specification is 0.039 % + 6 mV as the 0.039 % is the same, and the floor is twice the value (2 x 3 mV).

AUX (50th Harmonic) Output:

100 mV, 5 kHz From "AC Voltage (Sine Wave) 90 Day Specifications" the auxiliary output specification for 100 mV, 5 kHz, is 0.15 % + 450 μ V. For the dual output in this example, the specification is 0.15 % + 900 μ V as the 0.15 % is the same, and the floor is twice the value (2 x 450 μ V).

AC Voltage (Sine Wave) Extended Bandwidth

| Range | Frequency | 1-Year Absolute Uncertainty tcal $\pm 5^\circ\text{C}$ | Max Voltage Resolution |
|--|--------------------|---|-------------------------|
| Normal Channel (Single Output Mode) | | | |
| 1.0 to 33 mV | 0.01 to 9.99 Hz | $\pm(5.0\%$ of output $+0.5\%$ of range) | Two digits, e.g., 25 mV |
| 34 to 330 mV | | | Three digits |
| 0.4 to 33 V | | | Two digits |
| 0.3 to 3.3 V | 500.1 kHz to 1 MHz | -10 dB at 1 MHz, typical | Two digits |
| | 1.001 to 2 MHz | -31 dB at 2 MHz, typical | |
| Auxiliary Output (Dual Output Mode) | | | |
| 10 to 330 mV | 0.01 to 9.99 Hz | $\pm(5.0\%$ of output $+0.5\%$ of range) | Three digits |
| 0.4 to 5 V | | | Two digits |

AC Voltage (Non-Sine Wave)

| Triangle Wave & Truncated Sine Range, p-p ^[1] | Frequency | 1-Year Absolute Uncertainty, tcal $\pm 5^\circ\text{C}$, $\pm(\%$ of output + $\%$ of range) ^[2] | Max Voltage Resolution |
|--|------------------------------|--|--------------------------|
| Normal Channel (Single Output Mode) | | | |
| 2.9 to 92.999 mV | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz ^[3] | 5.0 + 0.5 | |
| 93 to 929.999 mV | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz ^[3] | 5.0 + 0.5 | |
| 0.93 to 9.29999 V | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz ^[3] | 5.0 + 0.5 | |
| 9.3 to 93 V | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz ^[3] | 5.0 + 0.5 | |
| Auxiliary Output (Dual Output Mode) | | | |
| 29 to 929.999 mV | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |

| | | | |
|---|----------------|-------------|--------------------------|
| 0.93 to 9.29999 V | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz | 5.0 + 0.5 | |
| | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz | 5.0 + 0.5 | |
| <p>[1] To convert p-p to rms for triangle wave, multiply the p-p value by 0.2886751. To convert p-p to rms for truncated sine wave, multiply the p-p value by 0.2165063.</p> <p>[2] Uncertainty is stated in p-p. Amplitude is verified using an rms-responding DMM.</p> <p>[3] Uncertainty for Truncated Sine outputs is typical over this frequency band.</p> | | | |

AC Voltage (Non-Sine Wave) (cont.)

| Square Wave Range (p-p) ^[1] | Frequency | 1-Year Absolute Uncertainty, tcal ±5 °C, ±(% of output + % of range) ^[2] | Max Voltage Resolution |
|--|----------------------------|---|--------------------------|
| Normal Channel (Single Output Mode) | | | |
| 2.9 to 65.999 mV | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz | 5.0 + 0.5 | |
| 66 to 659.999 mV | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz | 5.0 + 0.5 | |
| 0.66 to 6.59999 V | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz | 5.0 + 0.5 | |
| 6.6 to 66.0000 V | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 20 kHz | 0.5 + 0.25 | |
| | 20 to 100 kHz | 5.0 + 0.5 | |
| Auxiliary Output (Dual Output Mode) | | | |
| 29 to 659.999 mV | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz ^[3] | 5.0 + 0.5 | |
| 0.66 to 6.59999 V | 0.01 to 10 Hz | 5.0 + 0.5 | Two digits on each range |
| | 10 to 45 Hz | 0.25 + 0.5 | Six digits on each range |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz ^[3] | 5.0 + 0.5 | |
| <p>[1] To convert p-p to rms for square wave, multiply the p-p value by 0.5.</p> <p>[2] Uncertainty is stated in p-p. Amplitude is verified using an rms-responding DMM.</p> <p>[3] Limited to 1 kHz for Auxiliary outputs ≥6.6 V p-p.</p> | | | |

| Range ^[1] (Normal Channel) | Offset Range ^[2] | Max Peak Signal | 1-Year Absolute Uncertainty, tcal $\pm 5\text{ }^\circ\text{C}$ ^[3] $\pm(\%$ of dc output + floor) |
|--|-----------------------------|-----------------|--|
| Sine Waves (rms) | | | |
| 3.3 to 32.999 mV | 0 to 50 mV | 80 mV | 0.1 + 33 μV |
| 33 to 329.999 mV | 0 to 500 mV | 800 mV | 0.1 + 330 μV |
| 0.33 to 3.29999 V | 0 to 5 V | 8 V | 0.1 + 3300 μV |
| 3.3 to 32.9999 V | 0 to 50 V | 55 V | 0.1 + 33 mV |
| Triangle Waves and Truncated Sine Waves (p-p) | | | |
| 9.3 to 92.999 mV | 0 to 50 mV | 80 mV | 0.1 + 93 μV |
| 93 to 929.999 mV | 0 to 500 mV | 800 mV | 0.1 + 930 μV |
| 0.93 to 9.29999 V | 0 to 5 V | 8 V | 0.1 + 9300 μV |
| 9.3 to 93.0000 V | 0 to 50 V | 55 V | 0.1 + 93 mV |
| Square Waves (p-p) | | | |
| 6.6 to 65.999 mV | 0 to 50 mV | 80 mV | 0.1 + 66 μV |
| 66 to 659.999 mV | 0 to 500 mV | 800 mV | 0.1 + 660 μV |
| 0.66 to 6.59999 V | 0 to 5 V | 8 V | 0.1 + 6600 μV |
| 6.6 to 66.0000 V | 0 to 50 V | 55 V | 0.1 + 66 mV |
| <p>[1] Offsets are not allowed on ranges above the highest range shown above.</p> <p>[2] The maximum offset value is determined by the difference between the peak value of the selected voltage output and the allowable maximum peak signal. For example, a 10 V p-p square wave output has a peak value of 5 V, allowing a maximum offset up to ± 50 V to not exceed the 55 V maximum peak signal. The maximum offset values shown above are for the minimum outputs in each range.</p> <p>[3] For frequencies 0.01 to 10 Hz, and 500 kHz to 2 MHz, the offset uncertainty is 5 % of output, $\pm 1\%$ of the offset range.</p> | | | |

AC Voltage, Square Wave Characteristics

| Risetime @ 1 kHz Typical | Settling Time @ 1 kHz Typical | Overshoot @ 1 kHz Typical | Duty Cycle Range | Duty Cycle Uncertainty |
|--------------------------------|--|---------------------------------|---|---|
| <1 μs | <10 μs to 1 % of final value | <2 % | 1 % to 99 % <3.3 V p-p. 0.01 Hz to 100 kHz | $\pm(0.02\%$ of period + 100 ns), 50 % duty cycle $\pm(0.05\%$ of period + 100 ns), other duty cycles from 10 % to 90 % |

AC Voltage, Triangle Wave Characteristics (typical)

| Linearity to 1 kHz | Aberrations |
|---|--|
| 0.3 % of p-p value, from 10 % to 90 % point | <1 % of p-p value, with amplitude >50 % of range |

AC Current (Non-Sine Wave)

| Triangle Wave & Truncated Sine Wave Range p-p | Frequency | 1-Year Absolute Uncertainty tcal $\pm 5\text{ }^\circ\text{C}$ $\pm(\%$ of output + % of range) | Max Current Resolution |
|---|----------------|--|---------------------------|
| 0.047 to 0.92999 mA ^[1] | 10 to 45 Hz | 0.25 + 0.5 | Six digits |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz | 10 + 2 | |
| 0.93 to 9.29999 mA ^[1] | 10 to 45 Hz | 0.25 + 0.5 | Six digits |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz | 10 + 2 | |
| [1] Frequency limited to 1 kHz with LCOMP on. | | | |

AC Current (Non-Sine Wave) (cont.)

| Square Wave Range p-p | Frequency | 1-Year Absolute Uncertainty tcal ±5 °C ±(% of output + % of range) | Max Current Resolution |
|-------------------------|----------------|---|------------------------|
| 0.047 to 0.65999 mA [1] | 10 to 45 Hz | 0.25 + 0.5 | Six digits |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz | 10 + 2 | |
| 0.66 to 6.59999 mA [1] | 10 to 45 Hz | 0.25 + 0.5 | Six digits |
| | 45 Hz to 1 kHz | 0.25 + 0.25 | |
| | 1 to 10 kHz | 10 + 2 | |

[1] Frequency limited to 1 kHz with LCOMP on.

AC Current, Square Wave Characteristics (typical)

| Range | LCOMP | Risetime | Settling Time | Overshoot |
|-----------------|-------|----------|-----------------------------|---------------------------|
| I <6 A @ 400 Hz | off | 25 µs | 40 µs to 1 % of final value | <10 % for <1 V Compliance |

AC Current, Triangle Wave Characteristics (typical)

| Linearity to 400 Hz | Aberrations |
|---|--|
| 0.3 % of p-p value, from 10 % to 90 % point | <1 % of p-p value, with amplitude >50 % of range |

Change #2, 572

On page 7-3, under **Performance Test**, replace the 5th row with:

| | | | |
|------------|------------|------------|------------|
| 3.299999 V | 1.000000 V | 0.999955 V | 1.000045 V |
|------------|------------|------------|------------|

On page 7-10, in **Table Error! Reference source not found.. Verification Tests for DC Current (AUX)**, replace the 6th and 7th rows with:

| | | | |
|-----------|------------|-------------|-------------|
| 20.5000 A | 10.9000 A | 10.89536 A | 10.90454 A |
| 20.5000 A | -10.9000 A | -10.90464 A | -10.89536 A |